THE FOURSTROKE ADVANTAGE

THEY'RE NOT SHY. THEY'RE JUST QUIET.

Strong, quiet and easy to transport, Mercury® FourStroke Portables are anything but lightweight when it comes to performance. Available in 2.5 to 25 horsepower, these FourStrokes incorporate the lessons we've learned in more than 65 years of perfecting outboard technology for the marine environment.

In short, we took championship-winning power and performance and made it everything a four-stroke should be:

Clean and Quiet **Reliable**
Fuel-Efficient **No Mixing of Gas and Oil**

Additionally, most manual-start FourStroke Portables feature a camshaft decompression system that makes them easier to start than competitive four-strokes.

MERCURY PORTABLES

LIGHTWEIGHT. HEAVY ON FEATURES.

- Easy one-handed operation.
- Through-prop exhaust on most models buries engine noise underwater for a quieter, more enjoyable experience.
- Multiple trim positions (including shallow-water drives on select models) provide optimum performance.
- Standard water-separating fuel filter to minimize debris and water in the engine on select models.
- Lanyard stop switch for added safety.

800-MERCURY mercurymarine.com

REMEMBER: LIFE VESTS FLOAT. YOU DON'T.

MERCURY PORTABLES

TAKE THE POWER WITH YOU.

DESIGNED TO BE QUICK ON THEIR FEET

AND ON YOURS.

Fast, reliable outboard power – you really can take it with you no matter where your boating adventures lead. With Mercury Portables you get the dependable power and performance you need without sacrificing convenience. With horsepower ranging from 2.5 to 25, Mercury Portables are made to fit in the back of your car as easily as they fit on the back of your boat.

All models offer quick, easy starts and a rubber-insulated transom mounting system to reduce vibration and driver fatigue. And many feature simple, one-handed operation with shift, throttle, steering, throttle friction, and stop controls all designed to fit in the palm of your hand.

After all, boating is supposed to be fun and easy. Tough, dependable Mercury Portables help you keep it that way.

MERCURY
#1 On The Water®

Mercury Marine, W6250 West Pioneer Road
P.O. Box 1939, Fond du Lac, WI 54936-1939

© 2006, Mercury Marine, All Rights Reserved. Printed in U.S.A.

Part# 90-8M1821006

MERCURY
#1 On The Water®

BIG PERFORMANCE IN A SMALLER OUTBOARD

Versatile, reliable and fuel-efficient Mercury Portables run laps around the competition. Literally. Available with horsepower ranging from 2.5 to 25, these high-performance powerhouses are designed to work harder than the average outboard.

Take our BigFoot Portables for example. With their oversized gear cases, larger props and greater gear reduction, BigFoot Portables are engineered to provide greater thrust, maneuverability and holding and stopping power. Their portable design makes them ideal for use on pontoons, light-duty commercial craft and inflatables, or as auxiliary power on sailing or fishing boats.

From the convenient tiller-handle controls to a beefed up transom assembly, the 9.9hp ProKicker is fisherman's dream. Built to handle the meanest whitecaps and get to the fish quicker, the Pro Kicker features a superfast power tilt, centering straps that keep the engine aligned while under main power and a four-blade, high thrust propeller for superior handling and ultra-slow trolling speeds.

Add in the fact that Portable FourStrokes can run off your main fuel source, and it's no wonder more and more fisherman and pro anglers are making our FourStroke Portables their kickers of choice.

THREE-YEAR CORROSION WARRANTY

Every Mercury engine is backed by the industry's only three-year corrosion failure limited warranty, further proving that we stand behind our power.

THREE-YEAR WARRANTY

Every Mercury FourStroke is backed by a limited three-year factory warranty.

CLEANEST BY FAR

All Mercury FourStrokes (except 15 hp) exceed the EPA emissions standards for 2008 and have received a CARB three-star ultra-low emissions rating. They're all clean and efficient but boast plenty of torque to keep it fun.

FOURSTROKE

	Propshaft Rated Horsepower	Full-Throttle RPM Range	Cylinders/ Displacement	Bore/Stroke	Ignition	Starting	Gear Ratio	Steering	Alternator System	Trim System	Dry Weight[1]	Recommended Boat Transom Height	Induction System	CARB[2] Star Rating	Recommended Oil	Limited Warranty
FOURSTROKE SPECIFICATIONS																
25 EFI	25 hp (18.6 kW)	5000 – 6000	3 (in-line) 32.1 cu in (526 cc)	2.40" x 2.36" (61 mm x 60 mm)	CDI w/electric spark advance	Electric (turn-key) or manual	1.92:1	Remote or tiller	15 amp (186 watt)	Manual or Power Trim	157 lb (71 kg)	15" (381 mm) 20" (508 mm)	2-valve single overhead cam design	3	Mercury 4-Stroke	3-year
15	15 hp (11.1 kW)	4500 – 5500	2 (in-line) 19.7 cu in (323 cc)	2.32" x 2.32" (59 mm x 59 mm)	CDI w/electric spark advance	Electric or manual	2.00:1	Remote or tiller	Manual 6 amp (76 watt)	5 & shallow-water drive	111 lb (50 kg)	15" (381 mm) 20" (508 mm)	2-valve single overhead cam design	2	Mercury 4-Stroke	3-year
15 BigFoot	15 hp (11.1 kW)	4500 – 5500	2 (in-line) 19.7 cu in (323 cc)	2.32" x 2.32" (59 mm x 59 mm)	CDI w/electric spark advance	Electric or manual	2.42:1	Remote or tiller	Electric 10 amp (126 watt)	5 & shallow-water drive	128 lb (58 kg)	15" (381 mm) 20" (508 mm)	2-valve single overhead cam design	2	Mercury 4-Stroke	3-year
9.9 Pro Kicker	9.9 hp (7.3 kW)	5000 – 6000	2 (in-line) 12.8 cu in (209 cc)	2.16" x 1.73" (55 mm x 44 mm)	CDI w/electric spark advance	Electric or manual	2.42:1	Remote or tiller	6 amp (76 watt) on electric-start model	Power Tilt (PK)	107 lb (49 kg)	20" (508 mm) 25" (635 mm)	2-valve single overhead cam design	3	Mercury 4-Stroke	3-year
9.9 BigFoot	9.9 hp (7.3 kW)	5000 – 6000	2 (in-line) 12.8 cu in (209 cc)	2.16" x 1.73" (55 mm x 44 mm)	CDI w/electric spark advance	Electric or manual	2.42:1	Remote or tiller	6 amp (76 watt) on electric-start model	5 & shallow-water drive (BF)	96 lb (44 kg)	20" (508 mm) 25" (635 mm)	2-valve single overhead cam design	3	Mercury 4-Stroke	3-year
9.9	9.9 hp (7.3 kW)	5000 – 6000	2 (in-line) 12.8 cu in (209 cc)	2.16" x 1.73" (55 mm x 44 mm)	CDI w/electric spark advance	Electric or manual	2.08:1	Remote or tiller	6 amp (76 watt) on electric-start model	5 & shallow-water drive	84 lb (38 kg)	15" (381 mm) 20" (508 mm) 25" (635 mm)	2-valve single overhead cam design	3	Mercury 4-Stroke	3-year
8	8 hp (5.9 kW)	5000 – 6000	2 (in-line) 12.8 cu in (209 cc)	2.16" x 1.73" (55 mm x 44 mm)	CDI w/electric spark advance	Electric or manual	2.08:1	Tiller	6 amp (76 watt) on electric-start model	5 & shallow-water drive	84 lb (38 kg)	15" (381 mm) 20" (508 mm)	2-valve single overhead cam design	3	Mercury 4-Stroke	3-year
6	6 hp (4.4 kW)	5000 – 6000	1 7.5 cu in (123 cc)	2.32" x 1.77" (59 mm x 45 mm)	CDI w/electric spark advance	Manual	2.15:1	Tiller	Opt 4 amp (50 watt) lighting 2 amp (25 watt) charging	6 & shallow-water drive	55 lb (25 kg)	15" (381 mm) 20" (508 mm)	2-valve pushrod	3	Mercury 4-Stroke	3-year
5	5 hp (3.7 kW)	4500 – 5500	1 7.5 cu in (123 cc)	2.32" x 1.77" (59 mm x 45 mm)	CDI w/electric spark advance	Manual	2.15:1	Tiller	Opt 4 amp (50 watt) lighting 2 amp (25 watt) charging	6 & shallow-water drive	55 lb (25 kg)	15" (381 mm) 20" (508 mm)	2-valve pushrod	3	Mercury 4-Stroke	3-year
4	4 hp (2.9 kW)	4500 – 5500	1 7.5 cu in (123 cc)	2.32" x 1.77" (59 mm x 45 mm)	CDI w/electric spark advance	Manual	2.15:1	Tiller	Opt 4 amp (50 watt) lighting 2 amp (25 watt) charging	6 & shallow-water drive	55 lb (25 kg)	15" (381 mm) 20" (508 mm)	2-valve pushrod	3	Mercury 4-Stroke	3-year
3.5	3.5 hp (2.6 kW)	5000 – 6000	1 5.2 cu in (85 cc)	2.16" x 1.42" (55 mm x 36 mm)	CDI w/electric spark advance	Manual	2.15:1	Tiller	N/A	4	38 lb (17 kg)	15" (381 mm) 20" (508 mm)	2-valve pushrod	3	Mercury 4-Stroke	3-year
2.5	2.5 hp (1.9 kW)	5000 – 6000	1 5.2 cu in (85 cc)	2.16" x 1.42" (55 mm x 36 mm)	CDI w/electric spark advance	Manual	2.15:1	Tiller	N/A	4	38 lb (17 kg)	15" (381 mm)	2-valve pushrod	3	Mercury 4-Stroke	3-year